COTTER CORPORATION


PAPOOSE LIMESTONE MINE San Juan County, Utah

> Large Mine Application May, 1995

D I A L 3 O 3 - 8 6 4 - 7 3 4 7
P. O. BOX 700 — AIRPORT ROAD
N U C L A, C O L O R A D O 8 1 4 2 4

May 18, 1995

Anthony A. Gallegos Reclamation Engineer Utah Department of Natural Resources Division of Oil, Gas and Mining 355 West North Temple 3 Triad Center, Suite 350 Salt Lake City, UT 84180-1203



RE: Notice of Intention to Commence Large Mining Operations on State Lease ML-45609, San Juan County, Utah

Dear Mr. Gallegos:

Enclosed is a completed form MR-LMO including a Mine Plan, Maps and associated soils and vegetation data. Hopefully, reference within the application to the Mine Plan and Exhibits will not be too confusing. The proposed project will allow Cotter Corporation to supply an increase in demand for our limestone produced under Small Mine Permit No. 5/037/084.

A copy of this application and Mine Plan has been sent to Mr. John Blake of the Utah School and Institutional Trust Land Administration.

Cotter Corporation has also submitted a new application to the Utah Department of Environmental Quality (Division of Air Quality) now under Intent to Approve Order No. DAQE-378-95 to cover the possible increase in production.

As we discussed in our last telephone conversation, Cotter will probably require a variance concerning topsoil replacement during reclamation. I look forward to your inspection visit as soon as possible to discuss the issue in detail.

Should you have any questions or comments in the interim, please contact Jon Showalter at Cotter's Nucla Office, P.O. Box 700, Nucla, Colorado 81424, or call 970-864-7347.

Sincerely,

COTTER CORPORATION

Jon Showalter

Project Geologist

JS/tlt limeudnr.js FORM MR-LMO (Revised 1/92)

File #: M / /


Date Approved: / /

DOGM Lead:

ALSO SEE 5/057/084 FILE 5/057/084

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING

355 West North Temple 3 Triad Center, Suite 350 Salt Lake City, Utah 84180-1203 Telephone: (801) 538-5340



NOTICE OF INTENTION TO COMMENCE LARGE MINING OPERATIONS

The informational requirements in this form are based on provisions of the Mined Land Reclamation Act, Title 40-8, Utah Code Annotated 1953, General Rules and Rules of Practice and Procedures.

This form applies only to mining operations which disturb or will disturb greater than five acres at any given time.

"MINING OPERATIONS" means those activities conducted on the surface of the land for the exploration for, development of, or extraction of a mineral deposit, including, but not limited to, surface mining and the surface effects of underground and in situ mining, on-site transportation, concentrating, milling, evaporation, and other primary processing.

"Mining operation" does not include: the extraction of sand, gravel, and rock aggregate; the extraction of oil and gas as defined in Chapter 6, Title 40; the extraction of geothermal steam; smelting or refining operations; off-site operations and transportation; or reconnaissance activities which will not cause significant surface resource disturbance or involve the use of mechanized earth-moving equipment such as bulldozers or backhoes.

PLEASE NOTE:

If extra space is required to complete a section, please attach additional sheets and include cross-referenced page numbers as necessary. The operator may submit this information on an alternate form, however the same or similar format must be used.

I.	GENERAL INFORMATION (Rule R647-4-104)
1.	Mine Name: Papoose Mine
2.	Name of Applicant or Company: Cotter Corporation
	Corporation (X) Partnership () Individual ()
3.	Permanent Address: P.O. Box 700 28151 DD Road
	<u>Nucla, Colo. 81424</u> (970) 864-7347
4.	Company Representative (or designated operator):
	Name: Glen Williams
	Title: Manager, Western Slope Operations
	Address: P.O. Box 700, Nucla, CO 81424
	Phone: (970) 864-7347 FAX (970) 864-7287
6.	County(ies) San Juan Lisbon Valley 7.5 minute quadrangle NE 1/4 of NW 1/4, Section: 36 Township: 29½S Range: 24E NW 1/4 of NW 1/4, Section: 36 Township: 29½S Range: 24E SE 1/4 of NW 1/4, Section: 36 Township: 29½S Range: 24E SW 1/4 of NW 1/4, Section: 36 Township: 29½S Range: 24E NE 1/4 of SW 1/4, Section: 36 Township: 29½S Range: 24E NE 1/4 of SW 1/4, Section: 36 Township: 29½S Range: 24E Ownership of the land surface (circle which applies): Private (Fee), Public Domain (BLM), National Forest (USFS), State of Utah) or other:
	Name: Dept. of Natural Address: 355 West North Temple
	Name: Dept. of Natural Address: 355 West North Temple Name: Resources - Division Address: 3 Triad Center, Suite 400
	Name: of State Lands & Address: Salt Lake City, Utah 84180-1204
	Name Forestay Address:
7.	Owner(s) of record of the minerals to be mined: Name: State of Utah Address:
	Name: (as above) Address:
	Name: Address:
	Name: Address:
8.	Have the above owners been notified in writing? Yes X No No

	MAPS, DRAWINGS & PHOTOGRAPHS (Rule R647-4-105)	
1.	Base Map	
must The s series affect	mplete and correct topographic base map (or maps) with appropriate be submitted with this notice which show all of the items on the first scale should be approximately 1 inch = 2,000 feet (preferably a Use or equivalent topographic map where available) showing the located in sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit calculation of proposed surface distance in the sufficient detail to permit	SGS 7.5 minute tion of lands to be sturbance.
Pleas	se check off each section as it is drawn on the map(s). Does the m	nap show:
(a)	Property boundaries of surface ownership of all lands which are to be affected by the mining operations;	Exhibit C
(a) (b)	Property boundaries of surface ownership of all lands which are to be affected by the mining operations; Perennial streams, springs and other bodies of water, roads, buildings, landing strips, electrical transmission lines, water wells, oil and gas pipelines, existing wells or boreholes, or other existing surface or subsurface facilities within 500 feet of the proposed mining operations;	Exhibit C Exhibit B
	which are to be affected by the mining operations; Perennial streams, springs and other bodies of water, roads, buildings, landing strips, electrical transmission lines, water wells, oil and gas pipelines, existing wells or boreholes, or other existing surface or subsurface facilities	
(b)	which are to be affected by the mining operations; Perennial streams, springs and other bodies of water, roads, buildings, landing strips, electrical transmission lines, water wells, oil and gas pipelines, existing wells or boreholes, or other existing surface or subsurface facilities within 500 feet of the proposed mining operations; Proposed route of access to the mining operations from nearest publicly maintained highway (Map scale appropriate to	Exhibit B Exhibit C
(b) (c)	which are to be affected by the mining operations; Perennial streams, springs and other bodies of water, roads, buildings, landing strips, electrical transmission lines, water wells, oil and gas pipelines, existing wells or boreholes, or other existing surface or subsurface facilities within 500 feet of the proposed mining operations; Proposed route of access to the mining operations from nearest publicly maintained highway (Map scale appropriate to show access); Known areas which have been previously impacted by mining of	Exhibit B Exhibit C

Exhibit B

Man	Chec	klist
MINT	CIICO.	LLIDE

Please check off each section	as it is drawn	on the map.	Does the map show:
-------------------------------	----------------	-------------	--------------------

1 Icasc	CIRCLE OIL CHOIL BOOKING AS TO 12 TO	_
(a)	Proposed surface facilities, including but not limited to buildings, stationary mining/processing equipment, roads, utilities, power lines, proposed drainage control structures, and the location of topsoil storage areas, overburden/waste dumps, tailings or processed waste facilities, disposal areas for overburden, solid and liquid wastes, and wastewater discharge, treatment and containment facilities;	Exhibit B
(b)	A border clearly outlining the extent of the surface disturbed area proposed to be affected by mining, and the nu of acres proposed to be affected;	mber Exhibit B
(c)	The location of known test borings, pits, or core holes.	Exhibit B
3.	Additional Maps	
R64	itional maps and drawings may be required as applicable in acceptation of the second state of the second se	
1.	Mineral(s) to be mined:	
2.	Acreage to be disturbed: Includes existing mine di	sturbance
	Notice its (exempting storage disposal areas etc.):	19.84
	Minesite (operating, storage, disposal areas, etc.): Access/haul roads/conveyors:	0.16
	Associated on-site processing facilities:	0.00
	Associated on-site processing racing est. Total:	20.00
3.	Describe methods and procedures to be employed for min processing and concurrent reclamation. See part II Mine Plan under A. Operation and part VII Reclamation Plan under A. During Operation	

Elevation of groundwater (if known):	*	ft.
See Part V, Mine Plan (Water use, etc.)	0-12	inches
Thickness of soil material to be stockpiled:		niches
Area from which soil material can be salvaged:		0 cu. yds.
Volume of soil to be stockpiled: (cross reference with item IV-17)	_	<u>o</u> cu. yus.
Thickness of overburden:	none	ft.
Thickness of mineral deposit:	< 20	ft.
Volume of refuse, tailings, and processing waste stockpiles	:0	_ cu. yds.
Acreage and capacity of tailings ponds	0	acres
and water storage ponds to be constructed:		acres
	0	Acre-Feet
Describe how topsoil or subsoil material will be removed,	stockpiled	and Storm wa
protected: See Part II, Mine Plan under A. Operat	stockpiled	and . Storm wa
protected: See Part II, Mine Plan under A. Operat control.	stockpiled and E.	and . Storm wa
protected: See Part II, Mine Plan under A. Operat	stockpiled : ion and E. ockpiled: will be dis	posed of:

14. For each tailings pond, sediment pond, or other major drainage control structures, attach design drawings and typical cross-sections.

Vege	etation - The operator is required to return the land to a use ablish at least 70 percent of the premining vegetation groun	eful condition and cover.
vege	ground cover percentage figure is determined by sampling a tation type(s) on the areas to be mined (see Attachment I for pling methods).	and averaging to or suggested
(a)	<u>Vegetation Survey</u> - The following information needs to upon the vegetation survey:	be completed b
	Sampling method used Line intercept Number of plots or transects2	
	Ground Cover	Percent
	Vegetation (perennial grass, forb and shrub cover)	13.5
	Litter	25.5
	Rock/rock fragments	24
	Bare ground	37 100%
	200 8.000	
	Revegetation Requirement - 70 percent of above vegetation figure)	9.5
List	Revegetation Requirement - 70 percent	owing on the a

(b) Photographs - The operator may submit photographs (prints) of the site sufficient to show existing vegetation conditions. These photographs should show the general appearance and condition of the area to be affected and may be utilized for comparison upon reclamation of the site. Photographs should be clearly marked as to the location, orientation and the date that the pictures were taken.

inches cu. yds.

17.	Soils - The plan shall include an order 3 Soil Survey (or similar) and map. This information is needed to determine which soils are suitable for stockpiling for revegetation. This soil data may be available from the local Soil Conservation Service office, or if on public lands, from the land management agency. The map needs to be of such scale that soil types can be accurately determined on the ground (see Attachment I).
	(a) Each soil type to be disturbed needs to be field analyzed for the following:

Depth of soil material	<u>0-12</u> inches
Volume (for stockpiling)	< 17,000 cu. yds.
Texture (field determination)	<u>see exhibits D & E</u>
pH (field determination)	<u>see exhibits D & E</u>
(cross reference with item IV - 5)	
(01010	

Where there are problem soil areas (as determined from the field (b) examination) laboratory analysis may be necessary. Soil samples to be sent to the laboratory for analysis need to be about one pint in size, properly labeled, and in plastic bags. Each of the soil horizons on some sites may need to be sampled.

18.	Provide a narra	ative description of the geology of the area and/or a geologic	
	cross section:	See Part I, Overview of Mine Plan.	
			•
	«. 		

IMPACT ASSESSMENT (Rule R647-4-109) IV.

Please provide a general narrative description identifying potential surface and/or subsurface impacts. Where applicable, this description should include surface and groundwater systems, threatened or endangered species or their critical habitats, existing soil resources for reclamation, slope stability, erosion control, air quality, and public health and safety.

See Part II Mine Plan under E. Storm Water Control,	
Part V Water Use and Hydrologic Regime	
and Part VI Impact Assessment	

List current land use(s) other than mining:Cattle, deer and elk grazing
List future post-reclamation land-use(s) proposed: Cattle, deer and elk grazing.
Describe each phase of reclamation of the minesite in detail under the following categories:
Describe how buildings, foundations, trash and other waste materials will be disposed of. Any buildings will either be demolished and buried in pit or hauled off-site. All trash will be disposed of on-site or hauled to a proper facility.
(b) Backfilling and Grading Describe equipment and methods to be employed, amount of materials to be moved and final disposition of any stockpiled materials. Equipment used will be bulldozers and front-end loaders. Pit walls will be brought to 45 or less by backfilling of any rejected material which will require 7.4 cubic yards per linear foot of pit wall.
(c) Soil Material Replacement In order to reestablish the required ground cover, one to two feet (depending on underlying material) of suitable soil material usually has to be redistributed on the areas to be reseeded. If the stockpiled soil isn't sufficient for this, soil borrow areas will need to be located. How much soil material is planned to be put on the area to be reseeded?
(c) Soil Material Replacement In order to reestablish the required ground cover, one to two feet (depending on underlying material) of suitable soil material usually has to be redistributed on the areas to be reseeded. If the stockpiled soil isn't sufficient for this, soil borrow areas will need to be located. How much soil material is planned to be put on the area to be reseeded?
(c) Soil Material Replacement In order to reestablish the required ground cover, one to two feet (depending on underlying material) of suitable soil material usually has to be redistributed on the areas to be reseeded. If the stockpiled soil isn't sufficient for this, soil borrow areas will need to be located. How much soil material is planned to be put on the area to be reseeded? See Part VII, Mine Plan under C. Variance 12 inc.

spreading of topsoil either a harrow or d to loosen soil to a depth of 6".	isk will be employed
(The Division recommends ripping or discing six inch	es deep)
(e) <u>Seed Mixture</u> - List the species to be seeded: <u>Species Name</u>	Seeding Rate (lbs Pure Live Seed/Acre)
See Part VII Reclamation Plan	
under A. During Operation	
species of grass, forb, and browse seed and will prov requested)	tive and introduced adaptable ide a specific species list if
	ide a specific species list if
requested) (f) Seeding Method Describe method of planting the seed. Broadcast	seeded and harrowed or angeland or farm drill, or if
(f) Seeding Method Describe method of planting the seed. Red into soil ½" to ½". (The Division recommends planting the seed with a rebroadcast seeded, harrow or rake the seed 1/4 to 1/2 preferred time to seed) (g) Fertilization Describe fertilization method and rate. Monticello	seeded and harrowed or angeland or farm drill, or if inch into the soil. Fall is the
(f) Seeding Method Describe method of planting the seed. Red into soil ½" to ½". (The Division recommends planting the seed with a rebroadcast seeded, harrow or rake the seed 1/4 to 1/2 preferred time to seed)	seeded and harrowed or angeland or farm drill, or if inch into the soil. Fall is the

VI. <u>VARIANCE</u> (Rule R647-4-112)

Plugging Requirements), or Rule R647-4-111 (Reclamation Practices) must be identified below.

<u>Title/Category</u> Reclamation Practices
See Part VII Reclamation Plan
under C. Variance

For each variance requested, attach a narrative statement describing and delineating the area proposed to be affected by the variance, justifying the need for the variance, and discussing alternate methods or measures to be utilized.

VII. <u>SURETY</u> (Rule R647-4-113)

A Reclamation surety must be provided to the Division prior to final approval of this application. In calculating this amount, the Division will consider the following major steps:

- 1) Clean-up and removal of structures.
- 2) Backfilling, grading and contouring.
- 3) Soil material redistribution and stabilization.
- 4) Revegetation (preparation, seeding, mulching)

To assist the Division in determining a reasonable surety amount, please attach a reclamation cost estimate which addresses each of the above steps.

VIII. SIGNATURE REQUIREMENT

I hereby certify that the foregoing	is true and correct.
Signature of Operator/Applicant: _	Olen Wellians
Name (typed or print):	Glen Williams
Title/Position (if applicable):	Manager, Western Slope Operations
Date:	May 23, 1995
ACE MOTE	V

PLEASE NOTE:

Section 40-8-13(2) of the Mined Land Reclamation Act provides for maintenance of confidentiality concerning certain portions of this report. Please check to see that any information desired to be held confidential is so labeled and included on separate sheets or maps.

Only information relating to the <u>location</u>, size or nature of the <u>deposit</u> may be protected as confidential.

Confidential Information Enclosed: () Yes (X) No

I Overview

Cotter Corporation proposes to conduct a large scale shallow open pit limestone mining operation. The proposed mine is simply upgrading our present small scale operation at the same site due to an increase in demand for the limestone product. The limestone deposit consists of the upper unit of the Pennsylvanian aged Hermosa Formation. The land to be affected is Utah State land which is controlled by a State Lease. Accordingly, the Division of State Lands and Forestry has been given a copy of this proposed mine plan. The proposed mine site lies at an elevation ranging from 6650 to 6740 feet sloping from 8-16% to the west toward an unnamed intermittent The surface is 20-30% bare tributary of Big Indian Wash. limestone and 70-80% is covered with a very thin layer (usually less than 6") of soil. The mine area is vegetated at a moderate density by mature piñon and juniper trees with very sparse small shrubs and grass understory.

Limestone is the only mineral product to be mined. Any of the sparse topsoil to be stripped will be stockpiled and used later for reclamation purposes. The only waste rock types that will be generated consist of the possible fine rejects containing material from the very thin interbedded friable quartz sandstone lenses generated by the crushing and screening operation (described later) and minor amounts of are rejected quality due to material which (excessively weathered material, silica nodules, etc.) Much of the fine rejects will be used to surface the access road and storage area and potentially sold elsewhere for road base. A market for the coarse rejects, such as riprap use, will also be sought in order to minimize the amount of waste rock left Annual production is anticipated to be at the mine site. approximately 35,000 tons of limestone necessitating mining approximately 40,000 tons of rock per year.

II Mine Plan

A. Operation

The anticipated sequence for the mining operation will be as follows: Trees and brush will be stripped, windrowed or piled with a bulldozer. The thin, sporadic soil will be stripped and stockpiled. Blast holes will be drilled with an air track drill. The drill machine will be supplied with a vacuum dust collection system to prevent all but a very minute amount of dust to be produced. holes shot the Explosives will be loaded and In accordance with MSHA approximately once per month. regulations, any possible area of approach will be closed by barriers or fences and be guarded during blasting.

Limestone Mine Plan May 23, 1995 - Page 2

These fences and barriers will also hinder access to the highwall of the pit. It should be noted that the pit and highwalls are not expected to be more than 20 feet deep.

The broken rock will be mucked and trammed to the crusher by means of a rubber-tired loader. Rock will be crushed and screened to a product size of minus 10" to plus ½". This will require only a primary crushing operation employing a portable jaw crusher. Water spray devices will be used, as necessary, to minimize dust emissions during crushing. The particle size of the stockpiled material and any undersize reject pile should be large enough to preclude dust emissions due to wind. The undersize reject pile will be sprayed with water as necessary to control fugitive dust. Dust emissions will be regulated under Approval Order #DAQE-378-95 from the Utah Division of Air Quality.

The crushed product will be transported by conveyor or loader to the stockpile area. A berm has been constructed around this area as needed to prevent any mined material from washing down slope into the nearby drainage. The storage pad is of sufficient size (0.67 acre) to allow for truck turning and loading. The pit will then advance to the southeast. The crushing and stockpile areas will also move southeastward, within the pit boundary, periodically as needed.

B. Access

Access to the mine site is off San Juan county road #370 (Lisbon Valley Road) approximately 1.3 miles southeast of the intersection with San Juan county road #306 (Big Approximately 460 feet of new Indian Valley Road.) access road 20 feet wide has been constructed in accordance with the encroachment requirements of the San Juan county road department engineer. A culvert of appropriate size has been installed to cross the drainage on the south side of County road #370. Construction of the remaining 425 feet of access road to the stockpile and mine area (885 ft. total access road) consisted of upgrading an existing old seismic exploration road. dust suppressant will be applied as necessary to minimize the suspension of dust. The entire length of access road is located on the Utah State leased land. As a security measure, a gate has been installed on the northwest end of the mine area in order to deter access to the mine site by unauthorized persons.

Limestone Mine Plan May 23, 1995 - Page 3

C. Acreage of Disturbance

The acreage disturbed by the existing operation is estimated to be:

- A) Access road,
 - 1) new 0.16 acre,
 - 2) upgrade of existing road 0.20 acre, for a total of 0.36 acre,
- B) Storage Pad 0.67
- C) Topsoil Stockpile 0.83
- D) Mine area and area cleared prior to mining 3.1 acre.

Total number of acres presently disturbed	5 acre
Additional acres to be permitted	15 acre
Total number of acres to be permitted -	20 acre

D. Surface Facilities

At present, a small camper trailer is being utilized as a mine office and for storage of tools and a portable toilet. In the future, two small buildings may be either constructed on site or moved in. These will serve as storage for lubricants in one case and tools and other equipment in the other. A larger enclosed portable toilet may also be employed should on-site personnel requirements increase. A fueling station has been established within a bermed area to control spillage. (see attached surface facilities map)

E. Storm Water Control

During mining operations, the pit and crushing area will remain a sufficient distance east of the drainage to generally preclude the potential for sediment to enter surface waters of the state. Also, since the mining operation will be near the crest of the ridge, very little storm water runoff is anticipated to enter and subsequently exit the mine area. Additional berms and silt fence have been constructed below the crushing area to minimize sedimentation from this area leaving the site and reaching the nearby drainage. Any storm water is regulated under Storm Water Permit No. UTR000257, issued by the Utah Division of Water Quality.

All mine-related trash will be disposed of on-site or removed from the property by the completion of the operation. In addition, activities will be conducted so as not to present fire hazards. Portable toilet facilities will be provided during periods of operation.

III Exploration Drilling

Cotter Corporation is planning a small exploration drilling project of approximately 10 holes extending down the center of the proposed Large Mine area. This project has already received permit file number S/037/084 to be conducted during the 1995/1996 exploration season from the Utah Division of Oil, Gas and Mining.

IV Site Access Controls and Other Lessee Notifications

As previously mentioned, barriers, such as windrows of stripped trees, fences, gate and signs will be used to deter entry of the mining area by the public and livestock during mining and later reclamation as necessary. The other lease holders of this parcel of State Land have been notified of Cotter's intent and application for a Large Mining Permit. These other lessees (Paul D. Redd of Monticello, Utah - Grazing Permit, Union Oil of California in Houston, Texas - Oil, Gas and Hydrocarbons lease and Jerome B. Guinand of Sandy, Utah - Metalliferous Minerals Lease) will be allowed access to the mining area if needed. None of the fences will be constructed in such a manner as to deny livestock access to existing watering places. There will be no other disturbance to any of the other surface resources on this State lease outside the 20 acres covered by this permit application.

V Water Use & Hydrologic Regime

All water to be used in this operation is expected to be purchased from Redd Ranches in La Sal, Utah and hauled to the mine site. No ground water has been encountered in the mining operation. Since the mine site is near the crest of the ridge, there is insufficient recharge area to contribute ground water to the area, especially at the shallow pit depths of 20 feet or less. Furthermore, the limestone is impermeable, so recharge would only be through joints and fractures. The underlying sandstone is poorly cemented and very permeable, thereby allowing infiltration, so no seeps are anticipated even at the base of the limestone bed.

VI Impact Assessment

As previously stated, no adverse impacts are expected to surface or ground water regimes. Soil resources impacts will be addressed through a variance under "Reclamation Plan" (following) as are slope stability and erosion control. There have been no state or federal threatened and endangered species encountered and no potential impacts are expected.

VII Reclamation Plan

A. During Operation

Reclamation will be done concurrently with mining as much as possible once the pit is large enough. This is not expected to happen until the third year of operation. Before any portion of the pit is abandoned, the highwall will be cut or backfilled with course reject material to a slope of less than 45°. The available top soil will be spread and scarified, then seeded with the following seed mixture chosen from a list of species suggested by the U.S. Soil Conservation Service offices in Monticello, Utah and Norwood, Colorado.

Grasses:	lbs/acre (drilled)	lbs/acre (broadcast)
Crested Wheat Grass (Hycrest) Russian Wild Rye (Bozoisky) Pubescent Wheat Grass (Luna) Total Grasses		6 6 <u>8.4</u> 20.4
Forbs: Alfalfa (Spreader 2)	0.8	1.6
Shrubs: 4-Wing Salt Bush (Rincon)	0.5	1.0
Total	11.5 lb/acre	23.0 lb/acre

A few of the original trees will be scattered across any reclaimed areas.

During the third year of operations, reclamation should begin on previously mined areas. This will be conducted concurrently with pit advance so as not to exceed the permitted 20 acres before release of reclaimed acreage.

B. Final

Buildings will either be moved off the site, salvaged or demolished and covered over in the pit.

After mining operations cease and it is determined the access road and stockpile area are no longer needed (that is if the Utah Division of State Lands and Forestry does not want the road left in place) they will be reclaimed according to state reclamation standards.

Also, any remaining reject material resulting from sizing operations will be disposed of in the pit.

Limestone Mine Plan May 23, 1995 - Page 6


C. Variance


As the mining operations advance to the southeast, less and less topsoil cover will be encountered. Due to this, Cotter Corporation is requesting a variance under rule R647-4-111. If approved, the reclamation plan (in areas of thin topsoil) will be to concentrate the available soils into "islands" or isolated areas to provide the necessary soil requirements for generation of vegetation. These "islands" will be evenly scattered throughout the mined area.

As indicated in the Large Mine Permit application (under III. Operation part 16, Vegetation) two transects using the Line Intercept method to survey cover averaged 24% rock/rock fragments. In some of the worse areas the topsoil may range between 1"-6" in thickness. When considered the rough nature of the limestone surface immediately underlying the topsoil, it may not be feasible to reasonably separate the minimal amounts of topsoil from the limestone as the mine advances to the southeast boundary of the permit area. Due to these difficulties, we may be lucky to create 12" thick "islands" on 5% of the reclaimed acreage. Even at this low estimate, we should manage a net gain in available grazable vegetation when compared to the present conditions.

Berms and water bars may be placed where needed to prevent erosion during re-vegetation. This will also prevent sediment delivery to the nearby drainage. The land will thus be returned to the pre-mining use of livestock and wildlife grazing.


JS/tlt limemine.js





COTTER CORPORATION
PAPOOSE MINE PLAN
Large Mine Permit
1'=500'

1 topsoil storage



UNITED STATES DEPARTMENT OF AGRICULTURE NATURAL RESOURCES CONSERVATION SERVICE SECTION II-E TECHNICAL GUIDE

ECOLOGICAL SITE DESCRIPTION PINYON JUNIPER WOODLAND COLORADO FIELD OFFICE

Ecological Site Name: Shallow Loamy Mesa Top PJ #141

Ecological Site Number: GF - 039XY141C0

GF - 048XY141CO

Date: 03/01/95

Author's Initials: TO/CS/JA/DR/JH/BK

PART A: PHYSICAL CHARACTERISTICS

1. Soil Narrative:

- a. The soils in this site are shallow, well drained, and occur on gently sloping mesa tops. They formed in loess, colluvium and residual sandstone. Permeability is moderate above the bedrock. The available water capacity is very low. Erosion by water is slight to moderate and the hazard of erosion by wind is moderate. The natural soil fertility is low.
- b. List of Soil Taxonomic Units or Soil Mapping Units for all soils included in this site:

Soil	Surface	Slope	Phase	
Series	Texture	Ranges		
Longburn	CBV Sandy loam	1-12%	· · · -	
Arabrab	Fine sand	1-12%		
	Series	Series Texture Longburn CBV Sandy loam	Series Texture Ranges Longburn CBV Sandy loam 1-12%	

2. Landscape Factors

a. Physiography:

- 1. Elevation: Low: 7000 ft. High: 7800 ft.
- 2. Percent Slope: Low 1% High 12%
- 3. Nearly level to gently sloping areas on mesa tops.

3. Climate Factors

- a. Hard freeze free period: 180 to 220 days (24°F)
- b. Freeze-free period: 160 to 180 days (28°F)
- c. Frost-free period: 145 to 170 days (32°F)
- d. Mean annual precipitation: 15 to 18 inches
- e. Mean annual air temperature: 47 to 50°F
- f. Mean annual soil temperature: 49 to 52°F
- g. Moisture and temperature distribution:

	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
PPT HIGH MEAN LOW PERCENT	2.9 1.9 0.8 11	2.2 1.4 0.5 8	2.7 1.7 0.5 10			1.1 0.6 0.1 3	1.9		2.1 1.3 0.6 7	3.0 1.7 0.6 10	2.0 1.3 0.7 7	2.7 1.8 0.6 10
TEMP HIGH MEAN LOW	00 0	22 0	49.8 38.0 26.3	16 5	56 4	66 6	72.3	70.1	63.6	52.1	39.4	41.1 31.0 20.9

4. Vegetation Factors - Climax Plant Community:

a. Site Description Narrative:

When this site is at or near its potential, pinyon pine and Utah juniper dominate the site and make up over 80 percent of the plant community. Understory production is very limited and provides marginal amounts of forage for livestock and or wildlife. It does provide good escape cover and thermal cover for deer. When the tree canopy, cover exceeds 30 percent, diversity, both plant and animal, drops to its lowest level.

When the tree canopy ranges from 10 to 30 percent, a wide variety of grasses, forbs and shrubs will also be present in addition to the pinyon pine and Utah juniper.

Muttongrass, needleandthread, Indian ricegrass and bottlebrush squirreltail are the principal grasses. Forbs usually present include Wrights birdbeak, silvery lupine, rocky mountain penstemon, Crandall penstemon and Hoods phlox. Shrubs usually present include cliff fendlerbush, Torrey mormontea, low rabbitbrush, datil yucca, antelope bitterbrush, mountain mahogany and Utah serviceberry. During this tree canopy stage, diversity of plant and animal species will reach its peak.

When the tree canopy cover ranges from 0-10%, the previously mentioned species will generally be present with the grasses and forbs producing 80 to 90 percent of the total production. When the tree canopy level is reduced by fire, chaining and/or application of herbicides, forage production will be at its highest level for big game animals as well as domestic livestock.

b. Vascular Plant Community Composition (by air-dry weight):

Plant Symbol	Common Name	Productivity 0 -15 %	y by Canopy 15 -30%	Classes 30 - +%
GRASSES	AND GRASSLIKES			
POFE ORHY STCO4 ELEL5	MUTTONGRASS INDIAN RICEGRASS NEEDLEANDTHREAD BOTTLEBRUSH SQUIRRELTAIL	30 - 35 10 - 15 5 - 10 0 - 5	20 - 25 5 - 10 0 - 5 0 - 5	5 - 10 0 - 1 0 - 1 0 - 1
FORBS				
LUAR3 COWR2 SPCO PEST2 PECR5 ERUM PHHO COUM POAV PEPU7 PPFF	SILVERY LUPINE WRIGHT'S BIRDBEAK SCARLET GLOBEMALLOW ROCKY MOUNTAIN PENSTEMON CRANDALL PENSTEMON SULFUR BUCKWHEAT HOODS PHLOX BASTARD TOADFLAX PROSTRATE KNOTWEED ROCK GOLDENROD OTHER PERENNIAL FORBS	1 - 5 0 - 1 1 - 3 1 - 3 1 - 3 0 - 1 0 - 1 0 - 1 0 - 1 0 - 1	1 - 5 1 - 3 1 - 3 1 - 2 1 - 2 1 - 2 0 - 2 0 - 2 0 - 1 0 - 1	0 - 1 0 - 1
FERU EPTO CHHU2 YUBA PUTR2 CEMO2 AMUT	CLIFF FENDLERBUSH TORREY MORMONTEA* LOW RABBITBRUSH DATIL YUCCA* ANTELOPE BITTERBRUSH TRUE MOUNTAIN MAHOGANY UTAH SERVICEBERRY	0 - 3 0 - 3 0 - 5 0 - 3 0 - 3 0 - 3	0 - 5 0 - 5 0 - 5 0 - 5 0 - 5 0 - 5	0 - 2 0 - 1 0 - 1 0 - 1 0 - 1 0 - 1 0 - 1
TREES				
PIED JUOS	PINYON PINE UTAH JUNIPER	0 - 5 0 - 10	5 - 15 10 - 20	20 - 60 20 - 60

c. Total Annual Understory Production by Canopy Class in an Average Year: (all production below 4 1/2 feet, air-dry)

0	_	10%	650	to	800	lbs.	per	acre
10	_	30%	300	to				acre
30		+%	50	to	150	lbs.	per	acre

d. Total Annual Production by Canopy Class in an Average Year: (includes all overstory and understory production, air-dry)

0	_	15%	700	to	900	lbs.	per	acre
6 78		30%	600	to	800	lbs.	per	acre
		+%	450	to	700	lbs	per	acre

e. Animal Preference Values by Species 1/

		2.	ANIMAL	PREFERENCE	
Plant Symbol	Common Name		сѕн	GSS DEP BBM	
GRASSES	AND GRASSLIKES				
POFE ORHY ELEL5 STCO4	MUTTONGRASS INDIAN RICEGRASS BOTTLEBRUSH SQUIRRELTAIL NEEDLEANDTHREAD		P P P P P P D D D P D P	PPPDDDDPPDDDPDDDDDDDDDDDDDDDDDDDDDDDDD	
COWR2 LUAR3 SPCO PEST2 PECR5 ERUM PHHO COUM POAV PEPU7	WRIGHT'S BIRDBEAK SILVERY LUPINE SCARLET GLOBEMALLOW ROCKY MOUNTAIN PENSTEMON CRANDALL PENSTEMON SULFUR BUCKWHEAT HOODS PHLOX BASTARD TOADFLAX PROSTRATE KNOTWEED ROCK GOLDENROD			U U U D D D D D D D D D D D D D D D D D	
SHRUBS	& HALFSHRUBS				
AMUT FERU EPTO CHHU2 YUBA PUTR2 CEMO2	UTAH SERVICEBERRY CLIFF FENDLERBUSH TORREY MORMONTEA LOW RABBITBRUSH DATIL YUCCA ANTELOPE BITTERBRUSH TRUE MOUNTAIN MAHOGANY		D D U U D D D P D U D D P P D D P U	D D U D D D D D D D D D D D D D D D D D	5
TREES					4
PIED JUOS	PINYON PINE UTAH JUNIPER		ט ט ט ט ט ט		P D

UNITED STATES DEPARTMENT OF AGRICULTURE NATURAL RESOURCES CONSERVATION SERVICE SECTION II-E TECHNICAL GUIDE

ECOLOGICAL SITE DESCRIPTION PINYON JUNIPER WOODLAND COLORADO FIELD OFFICE

Ecological Site Name: Shallow Loamy Mesa Top PJ #141

Ecological Site Number: GF - 039XY141CO

GF - 048XY141CO

Date: 03/01/95

Author's Initials: TO/CS/JA/DR/JH/BK

PART A: PHYSICAL CHARACTERISTICS

1. Soil Narrative:

- a. The soils in this site are shallow, well drained, and occur on gently sloping mesa tops. They formed in loess, colluvium and residual sandstone. Permeability is moderate above the bedrock. The available water capacity is very low. Erosion by water is slight to moderate and the hazard of erosion by wind is moderate. The natural soil fertility is low.
- b. List of Soil Taxonomic Units or Soil Mapping Units for all soils included in this site:

SSA	Soil Series	Surface Texture	Slope Ranges	Phase
671 671	Longburn Arabrab	CBV Sandy loam Fine sand	1-12%	

2. Landscape Factors

a. Physiography:

- 1. Elevation: Low: 7000 ft. High: 7800 ft.
- 2. Percent Slope: Low 1% High 12%
- Nearly level to gently sloping areas on mesa tops.

3. Climate Factors

- a. Hard freeze free period: 180 to 220 days (24°F)
- b. Freeze-free period: 160 to 180 days (28°F)
- c. Frost-free period: 145 to 170 days (32°F)
- d. Mean annual precipitation: 15 to 18 inches
- e. Mean annual air temperature: 47 to 50°F
- f. Mean annual soil temperature: 49 to 52°F
- g. Moisture and temperature distribution:

	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
PPT HIGH MEAN LOW PERCENT	2.9 1.9 0.8 11	2.2 1.4 0.5 8	2.7 1.7 0.5 10	5 1 2 2 7 7 2 2 4 W	1.7 1.1 0.4 6	1.1 0.6 0.1 3	1.9	2.7 1.8 0.6 10	2.1 1.3 0.6 7	3.0 1.7 0.6 10	2.0 1.3 0.7 7	2.7 1.8 0.6 10
TEMP HIGH MEAN LOW	00 0	22 0	49.8 38.0 26.3	16 5	56 4	66 6	72.3	70.1	63.6	54.1	39.4	41.1 31.0 20.9

Vegetation Factors - Climax Plant Community:

a. Site Description Narrative:

When this site is at or near its potential, pinyon pine and Utah juniper dominate the site and make up over 80 percent of the plant community. Understory production is very limited and provides marginal amounts of forage for livestock and or wildlife. It does provide good escape cover and thermal cover for deer. When the tree canopy, cover exceeds 30 percent, diversity, both plant and animal, drops to its lowest level.

When the tree canopy ranges from 10 to 30 percent, a wide variety of grasses, forbs and shrubs will also be present in addition to the pinyon pine and Utah juniper.

Muttongrass, needleandthread, Indian ricegrass and bottlebrush squirreltail are the principal grasses. Forbs usually present include Wrights birdbeak, silvery lupine, rocky mountain penstemon, Crandall penstemon and Hoods phlox. Shrubs usually present include cliff fendlerbush, Torrey mormontea, low rabbitbrush, datil yucca, antelope bitterbrush, mountain mahogany and Utah serviceberry. During this tree canopy stage, diversity of plant and animal species will reach its peak.

When the tree canopy cover ranges from 0-10%, the previously mentioned species will generally be present with the grasses and forbs producing 80 to 90 percent of the total production. When the tree canopy level is reduced by fire, chaining and/or application of herbicides, forage production will be at its highest level for big game animals as well as domestic livestock.

b. Vascular Plant Community Composition (by air-dry weight):

Plant Symbol	Common Name	Productivit 0 -15 %	y by Canopy 15 -30%	Classes 30 - +%
GRASSES	AND GRASSLIKES			
POFE ORHY STCO4 ELEL5	MUTTONGRASS INDIAN RICEGRASS NEEDLEANDTHREAD BOTTLEBRUSH SQUIRRELTAIL	30 - 35 10 - 15 5 - 10 0 - 5		5 - 10 0 - 1 0 - 1 0 - 1
FORBS				
LUAR3 COWR2 SPCO PEST2 PECR5 ERUM PHHO COUM POAV PEPU7 PPFF	SILVERY LUPINE WRIGHT'S BIRDBEAK SCARLET GLOBEMALLOW ROCKY MOUNTAIN PENSTEMON CRANDALL PENSTEMON SULFUR BUCKWHEAT HOODS PHLOX BASTARD TOADFLAX PROSTRATE KNOTWEED ROCK GOLDENROD OTHER PERENNIAL FORBS	1 - 5 0 - 1 1 - 3 1 - 3 1 - 3 0 - 1 0 - 1 0 - 1 0 - 1 0 - 1	1 - 5 1 - 3 1 - 3 1 - 2 1 - 2 1 - 2 0 - 2 0 - 2 0 - 1 0 - 1	0 - 1 0 - 1
SHRUBS	& HALFSHRUBS			
FERU EPTO CHHU2 YUBA PUTR2 CEMO2 AMUT	CLIFF FENDLERBUSH TORREY MORMONTEA* LOW RABBITBRUSH DATIL YUCCA* ANTELOPE BITTERBRUSH TRUE MOUNTAIN MAHOGANY UTAH SERVICEBERRY	0 - 3 0 - 3 0 - 5 0 - 3 0 - 3 0 - 3	0 - 5 0 - 5 0 - 5 0 - 5 0 - 5 0 - 5	$ \begin{array}{cccc} 0 & - & 2 \\ 0 & - & 1 \\ 0 & - & 1 \\ 0 & - & 1 \\ 0 & - & 1 \\ 0 & - & 1 \end{array} $
TREES				
PIED JUOS	PINYON PINE UTAH JUNIPER	0 - 5 0 - 10	5 - 15 10 - 20	20 - 60 20 - 60
			TO SECURE THE PARTY OF THE PART	THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.

c. Total Annual Understory Production by Canopy Class in an Average Year: (all production below 4 1/2 feet, air-dry)

0	_	10%	650	to	800	lbs.	per	acre
10	_	30%	300	to				acre
30	u	+%	50	to	150	lbs.	per	acre

d. Total Annual Production by Canopy Class in an Average Year: (includes all overstory and understory production, air-dry)

71 10 10 10		+%	The state of the s		700		The Part of the Pa	
1 =		30%	600	to	800	lbs.	per	acre
0	_	15%	700	to	900	lbs.	per	acre

e. Animal Preference Values by Species 1/

		*	ANIMAL	PREFEREN	
Plant Symbol	Common Name		CSH	DEP	GSS BBM
GRASSES	AND GRASSLIKES				
POFE ORHY ELEL5 STCO4	MUTTONGRASS INDIAN RICEGRASS BOTTLEBRUSH SQUIRRELTAIL NEEDLEANDTHREAD		P P P P P P D D D P D P	P P P P D D D D D P D D	D D D D P P D D D U D D
FORBS					
COWR2 LUAR3 SPCO PEST2 PECR5 ERUM PHHO COUM POAV PEPU7	WRIGHT'S BIRDBEAK SILVERY LUPINE SCARLET GLOBEMALLOW ROCKY MOUNTAIN PENSTEMON CRANDALL PENSTEMON SULFUR BUCKWHEAT HOODS PHLOX BASTARD TOADFLAX PROSTRATE KNOTWEED ROCK GOLDENROD				D D D P P D D D D D D D D D D D D D D D
SHRUBS	& HALFSHRUBS				,
AMUT FERU EPTO CHHU2 YUBA PUTR2 CEMO2	UTAH SERVICEBERRY CLIFF FENDLERBUSH TORREY MORMONTEA LOW RABBITBRUSH DATIL YUCCA ANTELOPE BITTERBRUSH TRUE MOUNTAIN MAHOGANY		D D U U D D D P D D D D P P D D P U	D D U U D U D P P U D N D D D P P P D P P	D D D U U U D D D D D D D D D P P P D D P
TREES				20/1	
PIED JUOS	PINYON PINE UTAH JUNIPER		υ ὑ υ υ υ υ	U U U D D U	P P P D P D

+ opsoil stockeile Cross-sectional Views Before rechampshion Following initlad recdamation 4 Æ Plan View Macess .

EXHIBIT F

Papoose Limestone Mine Reclamation Plan

perator coff	er Corporati	ión	Date may	26,1995
O		FROM_		
MULTI		T TRACKING SH		X EXPANDABL APPROVED NOI
Description			YEA	R-Record Numb
¥NOI	Incoming	Outgoing	Internal	Superceded
NOT				
NOI	Incoming	_Outgoing	Internal	Superceded
NOI	Incoming	_Outgoing	Internal	Superceded
NOI	Incoming	Outgoing	Internal	Superceded
		_		
TEXT/ 81/	⁷ 2 X 11 MAP PA	AGES11	X 17 MAPS	LARGE MAP
OMMENTS: _				